



SANIT WC element INEO SCAN



Item number

Product description

90,736,00,,0000

WC element INEO SCAN

with water connection in the cistern h/w/d: 1,120/525/135 mm, for wall-hung WC with mounting distance 180/230 mm, front-operated, adjustment range front to wall: 135-205 mm, incl. 4 wall brackets (no foot fixation to the unfinished floor necessary), SANIT concealed cistern with insulation against condensation (CC-122-S-FO-2V-2C), with dual flush (6-4.5I/4-2I) and flexible cable technology, factory setting 6 and 3 litres, can be upgraded for shower WCs, fill valve Noise Class I, angle valve connection set for internal connection, protection box for access opening can be cut to size, flexible hose to fill valve, can be screwed by hand, 2 M12 WC retaining bolts, installation instructions, without push plate, packed in a box Concealed cistern tested to DIN EN 14055, Noise Class I, SINTEF, ETA Accessories:

- fastenings (wall brackets, feet, bottom wall bracket)
- WC flush actuators
- sound-absorbing sets
- WC connectors (double bend, offset connection bend, etc.) odour exhaust sets code no. 05.020.00..0000 plasterboard cladding panel code no. 17.115.00..S000
- roughing-in set for shower toilet code no. 03.956.00..0000 adjustable flush reducer code no. 05.261.00..0000